

Natural Hybrid Technical Data



Australian Range

	Standard	Result
Tile Size (mm)		1,800 x 177.8mm
Total Thickness (mm)		7.0 mm (5.5+1.5mm IXPE Backing)
Wear Layer Thickness (mm)		0.5 mm
Weight (±50 gr/m ²)	EN 430	9.75kgs / m ²
Box Quantity		6 Planks / 1.92 m ²
Dimension Squareness and Straightness	EN 431	Squareness: 0.18mm
		Straightness: 0.07mm
Impact Sound Reduction	ISO 16283-2:2015 & 717-2:2013	L'nT,w 51
Dimension Stability	EN 434	0.1%
Color Fastness To Light	ISO 105 B02	≥ Grade6
Wear Resistance	EN 660-1	Weargroup: T
Scratch Resistance	ISO 10582	3500g
Slip Resistance	AS 4586-2013	P4 / 46
Fire Rating	AS ISO 9239.1 2003	Critical Radiant Flux >11kw/m ²
		Smoke Developed Index 105%.m
Resistance To Chemical	EN 423	Pass
Residual Indentation	EN 433	Pass, 0.06mm
Environmental	Floor score (SCS-EC10.3-2014 v4.0)	Indoor Air Quality Certified; low VOC emissions

Oak Range

Tile Size (mm)		1,500 x 177.8mm
Total Thickness (mm)		8.0 mm (6.5+1.5mm IXPE Backing)
Wear Layer Thickness (mm)		0.5 mm
Weight (±50 gr/m ²)	EN 430	13.00 kgs / m ²
Box Quantity		6 Planks / 1.6 m ²



For more information  **07 3488 8115**

Email info@decoline.com.au Visit www.decoline.com.au